

**PRODUCT CODE: 161315****Petroleum Ether 40-60°C for synthesis**

TARIC 2710 12 25 99

Hydrocarbons mixture, mainly n-Pentane and 2-Methylpentane and less amounts of iso-Pentane , 2,2-and 2,3-Dimethylpentane and 3-Methylpentane .

SYNONYMS: Ligroin, Naphtha, Petroleum Benzin

PHYSICAL DATA: liquid, Clear, Colourless, Insoluble in water D (15 °C) 0,65 • B.P.: 40 - 60 °C • n20/D : 1,363 • Flash P.: -21 °C • Ign. T.: 245 °C • Vap. press. (20 °C) 350 hPa • Viscosity 25 °C 0,25 mPa.s • D. M. 20 °C 0 Debye • Expl. limit 1% (V) / 7% (V) •

BIBLIOGRAPHY: Merck Index 12, 5.513 13, 5.510 Safety 2 , 2733 B • Römp 8 , 909 • Kühn-Birett K 32 • ACS XI • ISO 6353/3-1987 R - 73 , 43 • DAB 1999 •

HAZARDOUS: C.E: 649-328-00-1 • RTECS: OI 6180000 • LD50 oral rat 2.000 mg/kg • LD50 oral rat >2.000 mg/kg • LC50 rat 54 mg/l / 4h • LD50 skn rbt 4.000 mg/kg • PEL n-pentane 1.000 ppm / 3.000 mg/m³

Derived No Effect Level (DNEL)

iso-pentane Population, oral, long term (systemic) 1301mg/kg bw/24h Population, Dermal, long exposure (systemic) 1377mg/kg bw/24h Workers Dermal, long exposure (systemic) 13964mg/kg bw/24h Population Inhalation, long term (systemic) 1.131 mg/m³ Workers Inhalation, long term (systemic) 5.306 mg/m³ n-pentane Population, oral, long term (systemic) 214mg/kg bw/24h Population, Dermal, long exposure (systemic) 214mg/kg bw/24h Workers Dermal, long exposure (systemic) 432mg/kg bw/24h Population Inhalation, long term (systemic) 643 mg/m³ Workers Inhalation, long term (systemic) 3.000 mg/m³



H: H225 • H315 • H304 • H336 • H411 •
P: P210 • P240 • P273 • P301+P310 • P331 • P403+P235 • P501 •

TRANSPORT REGULATIONS: UN: 1268 • ADR: 3/II • IMDG: 3/II • IATA: 3/II • PAX: 353 • CAO: 364 • (D/E) •

WEIGHT/VOLUME INFORMATION: 1l~0,645 kg 1kg~1,55 l

SPECIFICATIONS:

Density at 20/4	0,640-0,655
Range of Boiling	40-60°C
Non-volatile matter	0,002 %
Water (H ₂ O)	0,02 %

Ed.: 3 . Vig.: 15.01.2011 .

Prod.: 161315