

Safety data sheet
according to 1907/2006/EC, Article 31

Page 1/9

Printing date 25.06.2017
Revision: 25.06.2017
Version number 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

• **1.1 Product identifier**

• **Trade name:** Alkali Blue 6B solution

• **Article number:** 287101

• **Registration number**

A registration number is not available for this substance as the substance or its use are exempted from registration according to Article 2 REACH Regulation (EC) No 1907/2006, the annual tonnage does not require a registration, the registration is envisaged for a later registration deadline or it is a mixture.

• **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

• **Application of the substance / the mixture** Laboratory chemical

• **1.3 Details of the supplier of the safety data sheet**

• **Manufacturer/Supplier:**

AppliChem GmbH
Ottoweg 4
D-64291 Darmstadt

Tel.: +49 (0)6151 93570
Fax.: +49 (0)6151 935711
msds@applichem.com

• **Further information obtainable from:** Dept. Compliance

• **1.4 Emergency telephone number:** +49(0)6151 93570 (Inside normal business hours)

SECTION 2: Hazards identification

• **2.1 Classification of the substance or mixture**

• **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

• **2.2 Label elements**

• **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

• **Hazard pictograms**



GHS02 GHS07

• **Signal word** Danger

• **Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

• **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

GB

Trade name: Alkali Blue 6B solution

(Contd. of page 1)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-XXXX	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319	>50-<100%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-XXXX	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	>0.1-≤1%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Take affected persons out into the fresh air.
Keep quiet and cover.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Clean with water and soap. If possible, also wash with polyethylene glycol 400.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water.
Seek medical treatment.
- **After swallowing:**
Rinse out mouth.
make victim drink water (maximum of 2 drinking glasses)
If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
Dizziness
Dizziness
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**
Combustible.
Vapours are heavier than air and may spread along floors.
Forms explosive mixtures with air at ambient temperatures.

(Contd. on page 3)

Trade name: Alkali Blue 6B solution

(Contd. of page 2)

- Beware of backfiring.
Formation of toxic gases is possible during heating or in case of fire.
In case of fire, the following can be released:
carbon oxides (CO, CO₂).
- **5.3 Advice for firefighters**
 - **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
 - **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Avoid substance contact.
Protect against electrostatic charges.
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
Avoid substance contact.
Do not inhale steams/aerosols.
Ensure adequate ventilation
- **6.2 Environmental precautions:**
danger of explosion!
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (AppliSorb).
Ensure adequate ventilation.
Dispose of the material collected according to regulations.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Store in cool, dry place in tightly closed receptacles.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Work only in fume cupboard.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Provide solvent resistant, sealed floor.
Keep receptacles tightly sealed.
Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep away from open flames, hot surfaces and sources of ignition.
Store in cool, dry conditions in well sealed receptacles.
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
- **Recommended storage temperature:** +15 - +25 °C
- **Storage class:** 3

(Contd. on page 4)

Trade name: Alkali Blue 6B solution

(Contd. of page 3)

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm
Long-term value: 600 mg/m³, 200 ppm
Sk, BMGV

· DNELs

64-17-5 ethanol

Oral	Long-term - systemic effects, general population	87 mg/kg
Dermal	Acute - systemic effects, worker	343 mg/kg
	Long term - systemic effects, general population	206 mg/kg
Inhalative	Acute - local effects, worker	1900 mg/m ³
	Long-term - systemic effects, worker	950 mg/m ³
	Acute - local effects, general population	950 mg/m ³
	Long-term - systemic effects, general population	114 mg/m ³

· PNECs

64-17-5 ethanol

Aquatic compartment - freshwater	0.96 mg/L
Aquatic compartment - marine water	0.79 mg/L
Aquatic compartment - water, intermittent releases	2.75 mg/L
Aquatic compartment - sediment in freshwater	3.6 mg/kg
Terrestrial compartment - soil	0.63 mg/kg
Sewage treatment plant	580 mg/L
Oral secondary poisoning	0.72 mg/kg food

· Ingredients with biological limit values:

78-93-3 butanone

BMGV 70 µmol/L
Medium: urine
Sampling time: post shift
Parameter: butan-2-one

- **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

· Respiratory protection:

Filter A

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

Trade name: Alkali Blue 6B solution

(Contd. of page 4)

• **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **For the permanent contact gloves made of the following materials are suitable:**

Recommended thickness of the material: ≥ 0.7 mm

Butyl rubber, BR

Value for the permeation: Level ≥ 480 min

• **As protection from splashes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Value for the permeation: Level ≥ 120 min

• **Eye protection:**



Tightly sealed goggles

• **Body protection:**

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled.

SECTION 9: Physical and chemical properties

• **9.1 Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form: Fluid

Colour: Dark blue

• **Odour:** Like alcohol

• **Odour threshold:** Not determined.

• **pH-value at 20 °C:** 5.8

• **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 78 °C

• **Flash point:** 14 °C

• **Flammability (solid, gas):** Not applicable.

• **Ignition temperature:**

Decomposition temperature: Not determined.

• **Auto-ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

• **Explosion limits:**

Lower: 2.5 Vol %

(Contd. on page 6)

Trade name: Alkali Blue 6B solution

(Contd. of page 5)

Upper:	13.5 Vol %
· Vapour pressure at 20 °C:	57.3 hPa
· Density at 20 °C:	0.807 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Fully miscible.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	97.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** Forms explosive gas mixture with air.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Exothermic reactions with:
strong acids
alkaline earth metals
alkali metals
strong oxidants
- **10.4 Conditions to avoid**
Danger of receptacles bursting because of high vapour pressure when heated.
Forms explosive gas mixture with air.
- **10.5 Incompatible materials:**
Exothermic reactions with:
strong acids
strong oxidants
alkali metals
alkaline earth metals
- **10.6 Hazardous decomposition products:** In the event of fire: See chapter 5
- **Additional information:** Explosible with air in a vaporous/gaseous state.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**
Quantitative data on the toxicological effect of this product are not available.

Components	Type	Value	Species
64-17-5 ethanol			
Oral	LD50	8350 mg/kg (mouse) 10470 mg/kg (rat)	
Inhalative	LC50/4 h	116.9 mg/l (rat)	

(Contd. on page 7)

Trade name: Alkali Blue 6B solution

(Contd. of page 6)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **After inhalation:** No irritant effect.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

• **Carcinogenicity**

64-17-5 ethanol

NOAEL (carcinogenicity) >3000 mg/kg bw/day (rat)

Based on available data, the classification criteria are not met.

• **Reproductive toxicity**

64-17-5 ethanol

NOAEL (Fertility) 13800 mg/kg bw/day (mouse)

Based on available data, the classification criteria are not met.

- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.

Type of test	Effective concentration	Method	Assessment
--------------	-------------------------	--------	------------

64-17-5 ethanol

EC50/72 h	275 mg/l	(Algae)	
EC50/48 h	12900 mg/l	(Algae)	
LC50/24 h	11200 mg/l	(fish)	
LC50/48 h	12340 mg/l	(daphnia magna)	
LC50/96 h	13000 mg/l	(fish)	

- **12.2 Persistence and degradability** The product is easily biodegradable.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow to enter waters, waste water, or soil.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Chemicals must be disposed of in compliance with the respective national regulations.
Must not be disposed together with household garbage. Do not allow product to reach sewage system.



(Contd. on page 8)

Trade name: Alkali Blue 6B solution

(Contd. of page 7)

- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· 14.1 UN-Number	UN1993
· ADR, IMDG, IATA	
· 14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL))
· ADR, IMDG	
· IATA	FLAMMABLE LIQUID, N.O.S. (ETHANOL)
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
· EMS Number:	F-E, <u>S</u> -E
· Stowage Category	B
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L

(Contd. on page 9)

Trade name: Alkali Blue 6B solution

(Contd. of page 8)

· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL)), 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
- **Department issuing SDS:** Dept. Compliance
- **Contact:** Mr. Th. Stöckle
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

GB