

Safety Data Sheet
acc. to OSHA HCS

Page 1/9

Printing date 03/29/2018
Reviewed on 03/29/2018
Version number: 4

1 Identification

- **Product identifier**
- **Trade name:** 2-Propanol
- **Article number:** A3465
- **CAS Number:**
67-63-0
- **EC number:**
200-661-7
- **Index number:**
603-117-00-0
- **Application of the substance / the mixture**
Molecular biology
Biochemistry
Chemical analytics
Laboratory chemical
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
AppliChem GmbH
Ottoweg 4
D-64291 Darmstadt
- **Information department:** Dept. Compliance
- **Emergency telephone number:** +49(0)6151 93570 (Inside normal business hours)

Tel.: +49 (0)6151 93570
Fax.: +49 (0)6151 935711
msds@applichem.com

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 2 H225 Highly flammable liquid and vapor.
Eye Irrit. 2A H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements**
The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard statements**
H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
- **Precautionary statements**
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

Trade name: 2-Propanol

(Contd. of page 1)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Substances**
- **CAS No. Description**
67-63-0 2-Propanol
- **Identification number(s)**
- **EC number:** 200-661-7
- **Index number:** 603-117-00-0

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Wash off with plenty of water.
Immediately remove any clothing soiled by the product.
- **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.
Seek medical treatment.
- **After swallowing:**
make victim drink water (maximum of 2 drinking glasses)
Risk of aspiration!
Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Vapours are heavier than air and may spread along floors.
Forms explosive mixtures with air at ambient temperatures.
Formation of toxic gases is possible during heating or in case of fire.
CO, CO₂

(Contd. on page 3)

Trade name: 2-Propanol

(Contd. of page 2)

Combustible.

- **Advice for firefighters**

- **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

- **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Contain escaping vapours with water.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

Avoid substance contact.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (AppliSorb).

Ensure adequate ventilation.

Clean up affected area.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:** 400 ppm

- **PAC-2:** 2000* ppm

- **PAC-3:** 12000** ppm

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Avoid generation of vapours/aerosols.

Keep receptacles tightly sealed.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** Store in a cool location.

- **Information about storage in one common storage facility:**

Away from sources of ignition and heat.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Open receptacle only under localized extractor facilities.

Store only outside or in explosion proof rooms.

Store under lock and key and with access restricted to technical experts or their assistants only.

- **Recommended storage temperature:** +15 - +25°C

- **Storage class:** 3

- **Specific end use(s)** No further relevant information available.

— US —

(Contd. on page 4)

Trade name: 2-Propanol

(Contd. of page 3)

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:

67-63-0 2-Propanol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

Ingredients with biological limit values:

67-63-0 2-Propanol

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

- **Additional information:** The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

Breathing equipment:

Respiratory protection required when vapours/aerosols are generated.
Filter A

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.40 mm
Value for the permeation: Level ≥ 480 min

As protection from splashes gloves made of the following materials are suitable:

Recommended thickness of the material: ≥ 0.65 mm
Chloroprene rubber, CR
Value for the permeation: Level ≥ 120 min

Eye protection:



Tightly sealed goggles

(Contd. on page 5)

US

Trade name: 2-Propanol

(Contd. of page 4)

• **Body protection:**

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled.

9 Physical and chemical properties

• **Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form:

Fluid

Color:

Colorless

• **Odor:**

Alcohol-like

• **Odor threshold:**

Not determined.

• **pH-value:**

Not determined.

• **Change in condition**

Melting point/Melting range:

-89.5 °C (-129.1 °F)

Boiling point/Boiling range:

82 °C (179.6 °F)

• **Flash point:**

12-13 °C (53.6-55.4 °F)

• **Ignition temperature:**

425 °C (797 °F)

• **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

• **Explosion limits:**

Lower:

2 Vol %

Upper:

13.4 Vol %

• **Vapor pressure at 20 °C (68 °F):**

43 hPa (32.3 mm Hg)

• **Density at 20 °C (68 °F):**

0.785 g/cm³ (6.551 lbs/gal)

• **Solubility in / Miscibility with**

Water:

Fully miscible.

• **Partition coefficient (n-octanol/water):** 0.04999286

• **Viscosity:**

Dynamic at 20 °C (68 °F):

2.43 mPas

Kinematic:

Not determined.

• **Other information**

No further relevant information available.

10 Stability and reactivity

• **Reactivity** No dangerous reactions known.

• **Chemical stability**

• **Thermal decomposition / conditions to be avoided:**

Warming. A range from approx. 15 Kelvin below the flash point is to be rated as critical.

• **Possibility of hazardous reactions**

Forms explosive gas mixture with air.

Explosive reaction with oxidizing agents such as calcium chlorate and or peroxides.

• **Conditions to avoid** No further relevant information available.

• **Incompatible materials:**

Explosive reaction with oxidizing agents such as calcium chlorate and or peroxides.

• **Hazardous decomposition products:** In the event of fire: See chapter 5

US

(Contd. on page 6)

Trade name: 2-Propanol

(Contd. of page 5)

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values that are relevant for classification:

Components	Type	Value	Species
Oral	LD50	5,045 mg/kg (rat)	
Dermal	LD50	12,800 mg/kg (rabbit)	

- Primary irritant effect:
 - on the skin: No irritant effect.
 - on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
- Carcinogenic categories
- IARC (International Agency for Research on Cancer) 3
- NTP (National Toxicology Program) Substance is not listed.
- OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.

12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability Easily biodegradable
- Behavior in environmental systems:
- Bioaccumulative potential 0.05
- Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:
 - Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
 - Water hazard class 1 (Assessment by list): slightly hazardous for water
 - Do not allow to enter waters, waste water, or soil.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
- Recommendation:
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

- UN-Number
- DOT, ADR, IMDG, IATA UN1219

(Contd. on page 7)

Trade name: 2-Propanol

(Contd. of page 6)

- UN proper shipping name
- DOT, ADR
- IMDG, IATA

Isopropanol
ISOPROPANOL (ISOPROPYL ALCOHOL)

- Transport hazard class(es)
- DOT



- Class
- Label

3 Flammable liquids
3

- ADR



- Class
- Label

3 (F1) Flammable liquids
3

- IMDG, IATA



- Class
- Label

3 Flammable liquids
3

- Packing group

- DOT, ADR, IMDG, IATA

II

- Environmental hazards:

- Marine pollutant:

No

- Special precautions for user

Warning: Flammable liquids

- Danger code (Kemler):

33

- EMS Number:

F-E,S-D

- Stowage Category

B

- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

- Transport/Additional information:

- ADR

- Excepted quantities (EQ)

Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- IMDG

- Limited quantities (LQ)

1L

- Excepted quantities (EQ)

Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- UN "Model Regulation":

UN 1219 ISOPROPANOL, 3, II

—US—

(Contd. on page 8)

Trade name: 2-Propanol

(Contd. of page 7)

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):** Substance is not listed.
- **Section 313 (Specific toxic chemical listings):** Substance is listed.
- **TSCA (Toxic Substances Control Act):** Substance is listed.
- **Proposition 65**
- **Chemicals known to cause cancer:** Substance is not listed.
- **Chemicals known to cause reproductive toxicity for females:** Substance is not listed.
- **Chemicals known to cause reproductive toxicity for males:** Substance is not listed.
- **Chemicals known to cause developmental toxicity:** Substance is not listed.
- **Carcinogenity categories**
- **EPA (Environmental Protection Agency)** Substance is not listed.
- **TLV (Threshold Limit Value established by ACGIH) A4**
- **NIOSH-Ca (National Institute for Occupational Safety and Health)** Substance is not listed.
- **GHS label elements**
The substance is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard statements**
H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
- **Precautionary statements**
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Dept. Compliance
- **Date of preparation / last revision** 03/29/2018 / 3
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

(Contd. on page 9)

Trade name: 2-Propanol

(Contd. of page 8)

NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

• *** Data compared to the previous version altered.**

US